Advantage Series

RECIPROCATING AIR COMPRESSORS, 5–25 HP

- ► Ships Within 24 Hours
- ► 5 Year Warranty on Tank, Pump & Motors
- ► Pre-Installed Accessories
- ► Simplex & Duplex Configurations







The Advantages

A little over 90 years ago, Champion's amazing air compressors blazed new trails in the compressed air market. Today, Champion air compressors are still engineered with the same philosophy as we had back then. We design industrial grade air compressors for the professional.

The Champion Advantage Series offers a complete line of compressed air packages that meet any application. The Advantage Series has been carefully engineered to stand up to years of use.

Every Advantage Series compressor arrives with up to six standard, pre-installed accessories.

Standard Equipment Features

- Heavy Duty Two Stage, Splash Lubricated Air Compressor Pump(s)
- ► Multi-Finned Cylinders
- ► Integral Cylinder Head
- ► Intercoolers for Cooling Between Stages
- ► Reliable High Flow Disc Valves
- Oversized Main Bearings
- ▶ Balanced Crankshaft
- ▶ Oil Level Site Glass
- ► Centrifugal Unloader for Loadless Starting



- ▶ 0-300 PSIG Air Pressure Gauge
- ► Bucket High Drain Valve
- ► Factory Fill With ChampLub Lubricants
- OSHA Approved Belt Guard
- ► ASME Code Air Receiver
 - Pressure Relief Valve
 - Service Valve
 - Drain Valve
 - Pressure Gauge
- Vertical or Horizontal Configurations
- Oversize Inlet Filter Silencers
- Mounted Magnetic Starter
- ► Vibration Isolator Pads
- Automatic Tank Drain
- ► Low Oil Level Monitor
- ► Air Cooled Aftercooler (select models)
- Dual Control (select models)

Compressor Pump Warranty

Each new Champion Assembled Unit has a five (5) year warranty on the compressor pump only, against defects in materials or workmanship under normal use and service, from the date of installation or sixty-six (66) months from the date of shipment by Champion or a Champion distributor, whichever may occur first.

The five-year extended warranty covers parts and labor and is prorated over the five years as follows:

Year One — 100% coverage

Year Two — 90% coverage

Year Three — 80% coverage

Year Four — 70% coverage

Year Five — 60% coverage

Head valves are warranted for Year One only. Champion makes no warranty on components and/ or accessories furnished to Champion by third parties, such as electric motors, gasoline engines and controls. These are warranted only to the extent of the original manufacturer's warranty to Champion. Includes a five-year warranty on the air receiver, pump and motor.

Quality Accessories at a Glance



1 Magnetic motor starter

For thermal overload protection.

2 Air-cooled aftercooler

The factory mounted, heavy duty, air-cooled aftercooler effectively reduces up to 65% of the moisture from discharged compressed air. (select models)





3 Automatic tank drain

Automatically discharges excess moisture from the receiver.

4 Vibration isolator pads

Isolates the compressor unit from the foundation or floor. Reduces noise and protects the unit from any out-of-level floor situation that could cause vibration and damage.





5 Low oil level monitor

Low Oil Level Monitor shuts down the unit when oil levels are below an adequate level. Prevents the unit from restarting if oil levels are not at an adequate level.

6 Dual control

Allows compressor to run in start/stop or continuous run mode. (select models)

SIMPLEX TANK MOUNTED

Model #	HP	Variants		Pump		Tank Capacity		175 PSI	Dimensions	Weight
		STD	CA	Model #	Volts	Gallons*	RPM	Rating CFM Del'y	LxWxH	Approx. lbs
VR5-8	5	CASRSA01	CASRSA39	R-15B	230/1	80V	734	17.3	33 x 24 x 77	535
VR5-8	5	CASRSA126	CASRSA128	R-15B	230/1	80V	734	17.3	33 x 24 x 77	565
VR5-8	5	CASRSA05	CASRSA45	R-15B	208/3	80V	734	17.3	33 x 24 x 77	535
VR5-8	5	CASRSA03	CASRSA40	R-15B	230/3	80V	734	17.3	33 x 24 x 77	535
VR5-8	5	CASRSA148	CASRSA154	R-15B	230/3	80V	734	17.3	33 x 24 x 77	565
HR5-8	5	CASRSA07	CASRSA46	R-15B	230/1	80H	734	17.3	66 x 23 x 49	535
HR5-8	5	CASRSA146	CASRSA152	R-15B	230/1	80H	734	17.3	66 x 23 x 49	565
HR5-8	5	CASRSA11	CASRSA81	R-15B	208/3	80H	734	17.3	66 x 23 x 49	535
HR5-8	5	CASRSA09	CASRSA48	R-15B	230/3	80H	734	17.3	66 x 23 x 49	535
HR5-8	5	CASRSA147	CASRSA153	R-15B	230/3	80H	734	17.3	66 x 23 x 49	565
VR7F-8	7.5	CASRSA168	CASRSA167	R-15B	208/1	80V	990	23.1	33 x 24 x 77	545
VR7F-8	7.5	CASRSA13	CASRSA42	R-15B	230/1	80V	990	23.1	33 x 24 x 77	545
VR7F-8	7.5	CASRSA17	CASRSA53	R-15B	208/3	80V	990	23.1	33 x 24 x 77	545
VR7F-8	7.5	CASRSA15	CASRSA44	R-15B	230/3	80V	990	23.1	33 x 24 x 77	545
VR10-12	10	CASRSA21	CASRSA75	R-30D	208/3	120V	740	34.8	47 x 30 x 81	890
VR10-12	10	CASRSA19	CASRSA74	R-30D	230/3	120V	740	34.8	47 x 30 x 81	890
HR10-12	10	CASRSA25	CASRSA49	R-30D	208/3	120H	740	34.8	72 x 24 x 55	890
HR10-12	10	CASRSA29	CASRSA64	R-30D	208/3	120H	740	34.8	72 x 24 x 55	920
HR10-12	10	CASRSA23	CASRSA41	R-30D	230/3	120H	740	34.8	72 x 24 x 55	890
HR10-12	10	CASRSA27	CASRSA50	R-30D	230/3	120H	740	34.8	72 x 24 x 55	920
HRA15-12	15	CASRSA33	CASRSA59	R-40A	208/3	120H	770	53.7	74 x 28 x 62	1110
HRA15-12	15	CASRSA31	CASRSA43	R-40A	230/3	120H	770	53.7	74 x 28 x 62	1110
HRA25-12	25	CASRSA37	CASRSA65	R-70A	208/3	120H	770	90.1	74 x 27 x 64	1365
HRA25-12	25	CASRSA35	CASRSA47	R-70A	230/3	120H	770	90.1	74 x 27 x 64	1365

DUPLEX TANK MOUNTED

HR5D-12	5	CADRSA38	CADRSA46	R-15B	230/1	120H	734	34.6	70 x 28 x 55	980
HR5D-12	5	CADRSA83	CADRSA85	R-15B	208/3	120H	734	34.6	70 x 28 x 55	980
HR5D-12	5	CADRSA39	CADRSA47	R-15B	230/3	120H	734	34.6	70 x 28 x 55	980
HR7D-12	7.5	CADRSA40	CADRSA48	R-15B	230/1	120H	990	46.2	83 x 28 x 55	1305
HR7D-12	7.5	CADRSA84	CADRSA86	R-15B	208/3	120H	990	46.2	83 x 28 x 55	1305
HR7D-12	7.5	CADRSA41	CADRSA49	R-15B	230/3	120H	990	46.2	83 x 28 x 55	1305
HR10D-25	10	CADRSA54	CADRSA56	R-30D	230/3	250H	740	69.6	86 x 29 x 57	1725

^{*} V: Vertical, H: Horizontal Configuration



www. Champion Pneumatic.com

1301 North Euclid Avenue Princeton, Illinois 61356 USA www.ChampionPneumatic.com/ContactUs.aspx 866-276-4330









