

# LOW-RISE LIFTS

## Features


- 10,000 lbs. capacity or 7,000 lbs. capacity
- Drive-over ramps and side rails provide the width to support wider vehicles during approach
- Dual lifting cylinders provide the power required to lift a 10,000 lbs. vehicle
- The TL10 comes with four 3-position adapters, four 3" rubber blocks and four 1-1/2" rubber blocks for added height.



Shown: TL10111000  
10,000 lbs. capacity



- The TL07 comes with four 3" rubber blocks and four 1-1/2" rubber blocks.



Shown: TL07111000  
7,000 lbs. capacity

Specifications	TL10	TL07
Capacity	10,000 lbs.	7,000 lbs.
Rise High Step	30-5/16"	N/A
Rise Mid Step	28-5/16"	N/A
Rise Low Step	26-5/16"	N/A
Rise Tall Pad	24-3/4"	24-3/4"
Rise Short Pad	23-1/4"	23-1/4"
Rise Flat	21-3/4"	21-3/4"
Length Overall	90-1/2"	90-1/2"
Width Overall	78-1/2"	78-1/2"
Width Between Platforms	22-3/4"	22-3/4"
Length of Platforms	51-1/4"	51-1/4"
Length of Pad	17"	17"
Outside Width of Platforms	70-3/4"	70-3/4"
Horizontal Movement (during rise)	16"	16"
Collapsed Height	4"	4"
Locking Leg Heights	13-3/8"	13-3/8"
	17-3/8"	17-3/8"
	21-3/8"	21-3/8"
Voltage Single Phase	115v	115v
Time of Full Rise	40 seconds	40 seconds

Specifications subject to change without notice or liability.



Forward Lift  
996 Industrial Drive  
Madison, IN 47250

Phone: 800.423.1722  
Fax: 812.273.7329  
www.forwardlift.com



Lit# Forward Low&Mid-Rise\_2011.07

©2011 Vehicle Service Group<sup>SM</sup>  
Printed in the U.S.A. All rights reserved. Unless otherwise indicated, Forward Lift, Vehicle Service Group<sup>SM</sup>, Dover and all other trademarks are property of Dover Corporation and its affiliates.