

10,000 POUNDS **CAPACITY** 

LIGHT DUTY TWO POST LIFT

Designed to raise most passenger cars, trucks and vans.





Two-Post DP10AN200 is Gold Certified

Model DP10AN200 10,000 lbs. capacity

> Reliable, self-setting locking system with easy to reach lock

> > latch handle



Two heavy-duty Direct-Pull™ hydraulic cylinders designed to minimize down-time by requiring little maintenance

Padded shut-off bar - prevents

damage caused by lifting

a vehicle too high

Closed loop hydraulic system prevents hydraulic contamination Redesigned carriage - robust construction reformed for easier installation and routine maintenance

Adapter bracket included

Durable powder coat finish

Baseplate design compliant with International **Building Code** 

Spot-Rite™ 3-Stage Front Arms



**Engineering Excellence** 

Forward's U.S. engineers have decades of combined experience designing automotive lifts for service and repair shops. Forward's philosophy is to own our designs rather than use someone else's off the shelf product.

**Product Integrity** 

21st century design tools allow us to create, control and validate our designs to ensure maximum performance. Forward lifts are rigorously tested to meet quality and durability standards. All product families are proof load tested to 1½ times rated capacity and rigorously cycle tested.

Engineered to perform... Built to last!



# DP10/10,000 lbs. capacity two-post lifts

### Designed to raise most passenger cars, trucks and vans.

#### Features:

- Direct-Pull Lifting efficient, low maintenance technology
- Closed loop hydraulic system prevents oil contamination
- Padded overhead shut-off bar
- Spring operated arm restraints, disengage at floor level
- Single point lock release
- Rubber door bumper guard on carriage
- Durable powder coat finish
- ALI/ETL third party tested & approved
- Optional high rise and extended height available
- Optional screw-up truck adapters (1.25" / 32mm) available



Shown: Model DP10AN222
10,000 lbs. capacity extended height model with 3-stage front arms and frame engaging adapter accessories



## **Low-Profile Arm and Pad Design:** The DP10 features low-profile, oversized pads with multiple extensions to raise most vehicles on the road today. Includes four each of the following extensions shown: 1.75", 3.5" and 5" Optional screw-up truck adapters available. Includes rubber Shown with 5" adapter door bumper guard Spot-Rite™ 3-Stage Front **Arm Design**

The DP10 features offset arms to

accommodate vehicles both symmetrically and asymmetrically. This feature allows the technician to position the vehicle doors in front of or behind the column to prevent door damage.



Specifications	DP10A DP10A2HR
Capacity*	10,000 lbs. (4536kg)
Overall Height	143-3/8" (3642mm) 166-3/8" (4226mm)
Height to Shut-Off	137-3/4" (3499mm) 160-3/4" (4083mm)
Minimum Ceiling Height	144" (3658mm) 167" (4242mm)
Minimum Adapter Height (standard adapters)	3-5/8" (93mm)
Maximum Lifting Height High Rise (HR) Model Only	76" (1930mm) 79-1/2" (2019mm)
Adapter Extension Heights (stack type)	1-3/4" (45mm), 3-1/2" (90mm), 5" (130mm)
Front Arm Reach	23"- 44-1/2" (584mm - 1130mm)
Rear Arm Reach	38-1/2"- 58" (978mm - 1473mm)
Overall Floor Width	136.5" (3467mm) or optional 131.5" (3340mm)
Inside Column Width	114-1/2" (2908mm) or optional 108-1/2" (2756mm)
Drive Through	104-1/2" (2654mm) or optional 98-1/2" (2502mm)
Voltage†	208/230v
Amps	20
Motor	2 HP

Specifications subject to change without notice or liability. Standard lift colors include blue and red.

- \* Capacity 2500 lbs. per arm
- † single phase standard; 3-phase available at additional cost





Forward Lift 996 Industrial Drive Madison, IN 47250 Phone: 800.423.1722 Fax: 812.273.7329 www.forwardlift.com



Lit# Forward DP10A\_2013.06